

Heated oil Centrifuge



Features:

- Solid polyurethane injection molded housing.
- Circular bowl design offers a high-efficiency unit that meets ASTM D4007 requirements.
- Variable speed motor control allows for slow, smooth start.
- Safety lock lid keeps centrifuge closed during operation. Motor will not run while lid is open.
- Digital tachometer with LED readout shows real-time motor speed.
- Temperature controller with LED readout allows for precise control over bowl temperature.
- Digital timer with LED readout automatically stops motor when testing is complete
- IP 68 rated switches protect against dust and moisture to increase lifespan.
- Two independent electrical circuits reduce power load during operation.
- Power on indicator lamps for motor and heaters.

Power Source	230 VAC, 50/60 Hz
Bowl Heater	Yes
Pre-Heaters	N/A
Tube Style	100mL Long Cone
Tube Qty	4
Timer	Digital
Tachometer	Digital
Temperature Controller	Digital
Class 1, Division 2	No
Maximum RPM (RCF)	1750±50 (822±47)
Product Dimensions (in)	31.5L x 24.5W x 13.75H
Product Weight (lbs)	58



For, Canada & Middle East

AG Fuel Analytics Inc.
 E: sales@agfuelanalytics.com
 Ph: +1 2267007125 (Canada)
 Ph: +1 8482282828 (USA)